

Technical Data

Delivery Format

1 Packing with embossed carrier tape that enables automatic mounting

2 Reflow nut and self-tapping nut

- Through hole type can be attached with Kapton tape.
- Non-through hole type does not need to be attached with Kapton tape.

3 The size of reel for packaging use is $\Phi 380$ mm

- The number of products that can be packed by a single reel varies from product to product. Contact us.



Mounting on Substrate

The recommended substrate foot pattern, numerical aperture of metal mask, and tightening torque vary from product to product. Contact us.

Part Number Designation

SMAR-N10HT1500

a **b** **c** **d** **e** **f** **g**

a: Series Name

SMARX

c: Nut/Spacer Hole Size

Nut

Self Tapping

b: Products Category

N: Nut

S: Spacer

(Self Tapping)

10: M1.0

12: M1.2

14: M1.4

16: M1.6

20: M2.0

0F: No.0-80UNF

2C: No.2-56UNC

4C: No.4-40UNC

6C: No.6-32UNC

8C: No.8-32UNC

08: Hole size 0.8mm

10: Hole size 1.0mm

12: Hole size 1.2mm

14: Hole size 1.4mm

18: Hole size 1.8mm

d: Type

E: Press Working Upper/Lower Flange

F: Press Working Upper Flange

H: Half-Cut-Off

e: Hole Type

0: Through Hole

1: Non-Through Hole

T: Non-Through Hole Protruded End

f: Height

10: 1.0mm 25: 2.5mm

15: 1.5mm 30: 3.0mm

20: 2.0mm

g: Material and Finish Specification